

A		B		C	D	E	F
Parameters		Symbol	Minimum	Maximum			
1	Total Length	L	152.40	155.40			
	Threading Length	l	F.T	F.T			
	Major diameter	D	34.3900	34.8700			
	Pitch diameter	D1	32.6200	32.8100			
	Minor diameter	D2	30.9700	0.00			
	Chamfer	u	0.00	7.00			
	Thread per Inch	TPI	8 UNC				
2							
3							
4	Dimension as per		B 18.1.1				
	Chemical & Mechanical properties as per		ASTM A193				
	Thread tolerance class (C)		2A				
4	Grade		B16				
	Weight		0.96167 kg/piece				
Drawing Number				SIZE	TITLE		
KE-BASE-2200-00200-B18.1.1-A193-B16-1.3/8x6				1.3/8"x6"	Stud Bolt		
AMMENDMENT			Date - 24.07.2018		DIMENSIONS ARE IN MILLIMETERS		
DETAILS		REVISION	DATE				
REMOVE SHARP EDGES & BURRS		SHEET SIZE A4	SCALE NTS		ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS		
		Big Bolt Nut FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		<div style="border: 2px solid green; padding: 5px; display: inline-block;"> APPROVED </div>		KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	
A		B		C	D	E	F