

A		B		C	D	E	F
Parameters		Symbol	Minimum	Maximum			
1	Total Length	L	127.00	130.00			
	Threading Length	l	F.T	F.T			
	Major diameter	D	44.01	44.39			
	Pitch diameter	D1	42.14	42.33			
	Minor diameter	D2	40.50	-			
	Chamfer	u	0.00	9.00			
	Thread per Inch	TPI	8 UNC				
2					1		
3					2		
4					3		
4	Dimension as per		B 18.1.1		<p>'A' Enlarge View</p>		
	Chemical & Mechanical properties as per		ASTM A193				
	Thread tolerance class (C)		2A				
	Grade		B16				
4	Weight		1.31556 kg/piece		<p>APPROVED</p>		
Drawing Number				SIZE			
KE-BASE-2200-00246-B18.1.1-A193-B16-1.3/4x5				1.3/4"x5"	Stud Bolt	<p>Approved By Kapil Aggarwal CEO-MD</p> <p>Drawn By Pankaj Kumar (Sr. QC Manager)</p> <p>Checked BY Approved By Santosh Kumar</p>	
AMMENDMENT		Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS		<p>KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com</p>	
DETAILS		REVISION	DATE	<p>Big Bolt Nut</p> <p>FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS</p>		<p>ROLL FAST</p> <p>STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS</p>	
<p>REMOVE SHARP EDGES & BURRS</p>		SHEET SIZE	SCALE				
		A4	NTS				
A	B	C	D	E	F	5	