

A		B		C	D	E	F	
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>				
1	Total Length	L	158.75	161.75				
	Threading Length	l	F.T	F.T				
	Major diameter	D	47.19	47.57				
	Pitch diameter	D1	45.31	45.50				
	Minor diameter	D2	43.67	-				
	Chamfer	u	0.00	10.00				
	Thread per Inch	TPI	8 UNC					
2								
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		B16					
	Weight		2.03764 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00276-B18.1.1-A193-B16-1.7/8x6.1/4				1.7/8"x6.1/4"	Stud Bolt			
AMMENDMENT			Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS			
DETAILS		REVISION	DATE		Approved By Kapil Aggarwal CEO-MD		Drawn By Pankaj Kumar (Sr. QC Manager)	
					Checked BY Approved By Santosh Kumar			
<b>REMOVE SHARP EDGES &amp; BURRS</b>		SHEET SIZE A4	SCALE NTS		<b>ROLL FAST</b> <b>STAINLESS STEEL BOLTS</b> <b>HIGH TENSILE BOLTS</b> PRECISION TURNED COMPONENTS		<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	
5			<b>Big Bolt Nut</b> FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		APPROVED			
A		B		C	D	E	F	