

A		B		C	D	E	F
Parameters		Symbol	Minimum	Maximum			
1	Total Length	L	101.60	104.60			
	Threading Length	l	F.T	F.T			
	Major diameter	D	69.4100	69.7800			
	Pitch diameter	D1	67.5100	67.7200			
	Minor diameter	D2	65.8900	-			
	Chamfer	u	0.00	13.0000			
	Thread per Inch	TPI	8 UNC				
2							
3							
4	Dimension as per		B 18.1.1				
	Chemical & Mechanical properties as per		ASTM A193				
	Thread tolerance class (C)		2A				
4	Grade		B16				
	Weight		2.68606 kg/piece				
Drawing Number				SIZE	TITLE		
KE-BASE-2200-00367-B18.1.1-A193-B16-2.3/4x4				2.3/4"x4"	Stud Bolt		
AMMENDMENT			Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS		
DETAILS		REVISION	DATE		Approved By Kapil Aggarwal CEO-MD		
					Drawn By Pankaj Kumar (Sr. QC Manager)		
					Checked BY Approved By Santosh Kumar		
5	REMOVE SHARP EDGES & BURRS		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS		
	SHEET SIZE	SCALE		<div style="border: 2px solid green; padding: 5px; display: inline-block;"> APPROVED </div>			
	A4	NTS					
KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com							
A		B		C	D	E	F

'A' Enlarge View

APPROVED