


Parameters	Symbol	Minimum	Maximum
Total Length	L	95.25	98.25
Threading Length	l	F.T	F.T
Major diameter	D	27.41	28.52
Pitch diameter	D1	26.28	26.46
Minor diameter	D2	24.63	-
Chamfer	u	0.00	6.00
Thread per Inch	TPI	8 UNC	



Dimension as per	B 18.1.1
Chemical & Mechanical properties as per	ASTM A193
Thread tolerance class (C)	2A
Grade	B7
Weight	0.40168 kg/piece



Drawing Number <b>KE-BASE-2200-00141-B18.1.1-A193-B7-1.1/8x3.3/4</b>		SIZE <b>1.1/8"x3.3/4"</b>	TITLE <b>Stud Bolt</b>			
AMMENDMENT		Date - 19.07.2018	DIMENSIONS ARE IN MILLIMETERS			Approved By Kapil Aggarwal CEO-MD
DETAILS	REVISION	DATE	<b>ROLL FAST</b> STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	Drawn By Pankaj Kumar (Sr. QC Manager)		
<b>REMOVE SHARP EDGES &amp; BURRS</b>	SHEET SIZE <b>A4</b>	SCALE <b>NTS</b>		Checked BY Approved By Santosh Kumar		
		<b>Big Bolt Nut</b> FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS	<b>APPROVED</b>	<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com		