

A		B		C	D	E	F			
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>						
1	Total Length	L	254.00	257.00						
	Threading Length	l	F.T	F.T						
	Major diameter	D	27.41	28.52						
	Pitch diameter	D1	26.28	26.46						
	Minor diameter	D2	24.63	-						
	Chamfer	u	0.00	6.00						
	Thread per Inch	TPI	8 UNC							
2										
3										
4		Dimension as per		B 18.1.1						
		Chemical & Mechanical properties as per		ASTM A193						
		Thread tolerance class (C)		2A						
4		Grade		B7						
		Weight		1.07115 kg/piece						
5		Drawing Number			SIZE	TITLE				
		KE-BASE-2200-00160-B18.1.1-A193-B7-1.1/8x10			1.1/8"x10"	Stud Bolt				
		AMMENDMENT		Date - 19.07.2018		DIMENSIONS ARE IN MILLIMETERS				
		DETAILS	REVISION	DATE		<b>ROLL FAST</b> <b>STAINLESS STEEL BOLTS</b> <b>HIGH TENSILE BOLTS</b> PRECISION TURNED COMPONENTS	Approved By Kapil Aggarwal CEO-MD	Drawn By Pankaj Kumar (Sr. QC Manager)	Checked BY Approved By Santosh Kumar	
		<b>REMOVE SHARP EDGES &amp; BURRS</b>		SHEET SIZE A4			SCALE NTS	<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com		
				<b>Big Bolt Nut</b> FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS						
5										
A		B		C	D	E	F			