

A		B		C	D	E	F
Parameters		Symbol	Minimum	Maximum			
1	Total Length	L	107.95	110.95			
	Threading Length	l	F.T	F.T			
	Major diameter	D	31.32	31.70			
	Pitch diameter	D1	29.46	29.63			
	Minor diameter	D2	27.80	-			
	Chamfer	u	0.00	7.00			
	Thread per Inch	TPI	8 UNC				
2							
3							
4		Dimension as per		B 18.1.1			
		Chemical & Mechanical properties as per		ASTM A193			
		Thread tolerance class (C)		2A			
4		Grade		B7			
		Weight		0.56758 kg/piece			
5		Drawing Number		SIZE		TITLE	
		KE-BASE-2200-00168-B18.1.1-A193-B7-1.1/4x4.1/4		1.1/4"x4.1/4"		Stud Bolt	
		AMMENDMENT		Date - 19.07.2018		DIMENSIONS ARE IN MILLIMETERS	
		DETAILS		REVISION		DATE	
		REMOVE SHARP EDGES & BURRS		A4		SCALE NTS	
		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		APPROVED		ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	
						Approved By Kapil Aggarwal CEO-MD	
						Drawn By Pankaj Kumar (Sr. QC Manager)	
						Checked BY Approved By Santosh Kumar	
						KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	
A		B		C	D	E	F