

A		B		C	D	E	F	
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>				
1	Total Length	L	120.65	123.65				
	Threading Length	l	F.T	F.T				
	Major diameter	D	31.32	31.70				
	Pitch diameter	D1	29.46	29.63				
	Minor diameter	D2	27.80	-				
	Chamfer	u	0.00	7.00				
	Thread per Inch	TPI	8 UNC					
2								
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		B7					
	Weight		0.63435 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00170-B18.1.1-A193-B7-1.1/4x4.3/4				1.1/4"x4.3/4"	Stud Bolt			
AMMENDMENT			Date - 19.07.2018		DIMENSIONS ARE IN MILLIMETERS			
DETAILS		REVISION	DATE					
REMOVE SHARP EDGES & BURRS		SHEET SIZE A4	SCALE NTS		<b>ROLL FAST</b> <b>STAINLESS STEEL BOLTS</b> <b>HIGH TENSILE BOLTS</b> PRECISION TURNED COMPONENTS			
		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		APPROVED			<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	
A		B		C	D	E	F	