


A		B		C	D	E	F	
Parameters		Symbol	Minimum	Maximum				
1	Total Length	L	120.65	123.65				
	Threading Length	l	F.T	F.T				
	Major diameter	D	34.39	34.87				
	Pitch diameter	D1	32.62	32.81				
	Minor diameter	D2	30.97	-				
	Chamfer	u	0.00	7.00				
	Thread per Inch	TPI	8 UNC					
2								
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		B7					
	Weight		0.76132 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00195-B18.1.1-A193-B7-1.3/8x4.3/4				1.3/8"x4.3/4"	Stud Bolt			
AMMENDMENT			Date - 24.07.2018		DIMENSIONS ARE IN MILLIMETERS			
DETAILS		REVISION	DATE					
REMOVE SHARP EDGES & BURRS		SHEET SIZE A4	SCALE NTS		ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS			
		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		APPROVED			KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	
A		B		C	D	E	F	



'A' Enlarge View