

A		B		C	D	E	F
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>			
1	Total Length	L	127.00	130.00			
	Threading Length	l	F.T	F.T			
	Major diameter	D	37.66	38.04			
	Pitch diameter	D1	35.80	35.98			
	Minor diameter	D2	34.15	-			
	Chamfer	u	0.00	8.00			
	Thread per Inch	TPI	8 UNC				
2							
3							
4	Dimension as per		B 18.1.1				
	Chemical & Mechanical properties as per		ASTM A193				
	Thread tolerance class (C)		2A				
4	Grade		B7				
	Weight		0.97521 kg/piece				
Drawing Number				SIZE	TITLE		
KE-BASE-2200-00221-B18.1.1-A193-B7-1.1/2x5				1.1/2"x5"	Stud Bolt		
AMMENDMENT			Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS		
DETAILS		REVISION	DATE		Approved By		Checked BY
					Kapil Aggarwal CEO-MD		Santosh Kumar
					Drawn By		Approved By
					Pankaj Kumar (Sr. QC Manager)		Santosh Kumar
5	<b>REMOVE SHARP EDGES &amp; BURRS</b>		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		<b>ROLL FAST</b> <b>STAINLESS STEEL BOLTS</b> <b>HIGH TENSILE BOLTS</b> PRECISION TURNED COMPONENTS		<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com
A		B		C	D	E	F