

| A | | B | | C | D | E | F | |
|--|---|-------------------|------------------|-------------------------------|-----------|--|---|--|
| Parameters | | Symbol | Minimum | Maximum | | | | |
| 1 | Total Length | L | 228.60 | 231.60 | | | | |
| | Threading Length | l | F.T | F.T | | | | |
| | Major diameter | D | 44.01 | 44.39 | | | | |
| | Pitch diameter | D1 | 42.14 | 42.33 | | | | |
| | Minor diameter | D2 | 40.50 | - | | | | |
| | Chamfer | u | 0.00 | 9.00 | | | | |
| | Thread per Inch | TPI | 8 UNC | | | | | |
| 2 | | | | | | | | |
| 3 | | | | | | | | |
| 4 | Dimension as per | | B 18.1.1 | | | | | |
| | Chemical & Mechanical properties as per | | ASTM A193 | | | | | |
| | Thread tolerance class (C) | | 2A | | | | | |
| 4 | Grade | | B7 | | | | | |
| | Weight | | 2.36801 kg/piece | | | | | |
| Drawing Number | | | | SIZE | TITLE | | | |
| KE-BASE-2200-00258-B18.1.1-A193-B7-1.3/4x9 | | | | 1.3/4"x9" | Stud Bolt | | | |
| AMMENDMENT | | Date - 02.08.2018 | | DIMENSIONS ARE IN MILLIMETERS | | | | |
| DETAILS | REVISION | DATE | | | | | | |
| REMOVE SHARP EDGES & BURRS | | SHEET SIZE | SCALE | | | ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS | | KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com |
| A | | B | | C | D | E | F | |