

A		B		C	D	E	F	
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>				
1	Total Length	L	254.00	257.00				
	Threading Length	l	F.T	F.T				
	Major diameter	D	44.01	44.39				
	Pitch diameter	D1	42.14	42.33				
	Minor diameter	D2	40.50	-				
	Chamfer	u	0.00	9.00				
	Thread per Inch	TPI	8 UNC					
2					<p>'A' Enlarge View</p>			
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		B7					
	Weight		2.63112 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00260-B18.1.1-A193-B7-1.3/4x10				1.3/4"x10"	Stud Bolt			
AMMENDMENT		Date - 02.08.2018			DIMENSIONS ARE IN MILLIMETERS			
DETAILS	REVISION	DATE			<b>ROLL FAST</b> <b>STAINLESS STEEL BOLTS</b> <b>HIGH TENSILE BOLTS</b> PRECISION TURNED COMPONENTS	Approved By	Drawn By	Checked BY
						Kapil Aggarwal	Pankaj Kumar	Santosh Kumar
						CEO-MD	(Sr. QC Manager)	Approved By
<b>REMOVE SHARP EDGES &amp; BURRS</b>		SHEET SIZE	SCALE	<b>FASTENERS FOR WIND ENERGY</b> <b>ANCHOR BOLTS &amp; FOUNDATION BOLTS</b>		<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com		
		A4	NTS					
A	B	C	D	E	F			