

A		B		C	D	E	F	
Parameters		Symbol	Minimum	Maximum				
1	Total Length	L	228.60	231.60				
	Threading Length	l	F.T	F.T				
	Major diameter	D	50.36	50.74				
	Pitch diameter	D1	48.48	48.68				
	Minor diameter	D2	46.84	-				
	Chamfer	u	0.00	10.00				
	Thread per Inch	TPI	8 UNC					
4		Dimension as per		B 18.1.1				
		Chemical & Mechanical properties as per		ASTM A193				
		Thread tolerance class (C)		2A				
4		Grade		B7				
		Weight		3.11181 kg/piece				
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00308-B18.1.1-A193-B7-2x9				2"x9"	Stud Bolt			
AMMENDMENT		Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS				
DETAILS	REVISION	DATE						
REMOVE SHARP EDGES & BURRS		SHEET SIZE	SCALE			ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS		KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com
5		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS				5		
A		B		C	D	E	F	