

A		B		C	D	E	F
Parameters		Symbol	Minimum	Maximum			
1	Total Length	L	254.00	257.00			
	Threading Length	l	F.T	F.T			
	Major diameter	D	50.36	50.74			
	Pitch diameter	D1	48.48	48.68			
	Minor diameter	D2	46.84	-			
	Chamfer	u	0.00	10.00			
	Thread per Inch	TPI	8 UNC				
2					3		
3					4		
4					5		
Dimension as per		B 18.1.1		<p>'A' Enlarge View</p>			
Chemical & Mechanical properties as per		ASTM A193					
Thread tolerance class (C)		2A					
4	Grade	B7					
Weight		3.45755 kg/piece					
Drawing Number				SIZE	TITLE		
KE-BASE-2200-00310-B18.1.1-A193-B7-2x10				2"x10"	Stud Bolt		
AMMENDMENT		Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS		Approved By Kapil Aggarwal CEO-MD	
DETAILS	REVISION	DATE	Big Bolt Nut FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS	<div style="border: 2px solid green; padding: 5px; text-align: center; font-weight: bold; color: green;"> APPROVED </div>	ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	Drawn By Pankaj Kumar (Sr. QC Manager)	
REMOVE SHARP EDGES & BURRS		SHEET SIZE				SCALE	Checked BY Approved By Santosh Kumar
		A4	NTS			KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	
A	B	C	D	E	F		