

A		B		C	D	E	F
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>			
1	Total Length	L	158.75	161.75			
	Threading Length	l	F.T	F.T			
	Major diameter	D	63.06	63.44			
	Pitch diameter	D1	61.16	61.36			
	Minor diameter	D2	59.54	-			
	Chamfer	u	0.00	12.00			
	Thread per Inch	TPI	8 UNC				
2					<p><b>'A' Enlarge View</b></p>		
3							
4	Dimension as per		B 18.1.1				
	Chemical & Mechanical properties as per		ASTM A193				
	Thread tolerance class (C)		2A				
4	Grade		B7				
	Weight		3.42612 kg/piece				
Drawing Number				SIZE	TITLE		
KE-BASE-2200-00351-B18.1.1-A193-B7-2.1/2x6.1/4				2.1/2"x6.1/4"	Stud Bolt		
AMMENDMENT			Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS		
DETAILS		REVISION	DATE				
					<b>ROLL FAST</b> <b>STAINLESS STEEL BOLTS</b> <b>HIGH TENSILE BOLTS</b> PRECISION TURNED COMPONENTS		
5	<b>REMOVE SHARP EDGES &amp; BURRS</b>		SHEET SIZE	SCALE	<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com		
	A4	NTS		<b>Big Bolt Nut</b> FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS			
A		B		C	D	E	F