

A		B		C	D	E	F	
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>				
1	Total Length	L	304.80	307.80				
	Threading Length	l	F.T	F.T				
	Major diameter	D	63.06	63.44				
	Pitch diameter	D1	61.16	61.36				
	Minor diameter	D2	59.54	-				
	Chamfer	u	0.00	12.00				
	Thread per Inch	TPI	8 UNC					
2					<p>'A' Enlarge View</p>			
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		B7					
	Weight		6.57816 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00364-B18.1.1-A193-B7-2.1/2x12				2.1/2"x12"	Stud Bolt			
AMMENDMENT			Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS			
5	DETAILS	REVISION	DATE		<b>ROLL FAST</b> <b>STAINLESS STEEL BOLTS</b> <b>HIGH TENSILE BOLTS</b> PRECISION TURNED COMPONENTS	Approved By	Drawn By	Checked BY
	<b>REMOVE SHARP EDGES &amp; BURRS</b>	SHEET SIZE A4	SCALE NTS			FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS	KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	Kapil Aggarwal CEO-MD
A		B		C	D	E	F	