

A		B		C	D	E	F	
Parameters		Symbol	Minimum	Maximum				
1	Total Length	L	152.40	155.40				
	Threading Length	l	F.T	F.T				
	Major diameter	D	69.41	69.78				
	Pitch diameter	D1	67.51	67.72				
	Minor diameter	D2	65.89	-				
	Chamfer	u	0.00	13.00				
	Thread per Inch	TPI	8 UNC					
2								
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		B7					
	Weight		4.02909 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00375-B18.1.1-A193-B7-2.3/4x6				2.3/4"x6"	Stud Bolt			
AMMENDMENT			Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS			
DETAILS		REVISION	DATE					
REMOVE SHARP EDGES & BURRS		SHEET SIZE A4	SCALE NTS		Big Bolt Nut FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS			
		<div style="border: 2px solid green; padding: 5px; text-align: center; font-weight: bold; color: white;"> APPROVED </div>		ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS				
				KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com				
A		B		C	D	E	F	