

A		B		C	D	E	F																																																																																												
Parameters		Symbol	Minimum	Maximum																																																																																															
1	Total Length	L	171.45	174.45																																																																																															
	Threading Length	l	F.T	F.T																																																																																															
	Major diameter	D	69.41	69.78																																																																																															
	Pitch diameter	D1	67.51	67.72																																																																																															
	Minor diameter	D2	65.89	-																																																																																															
	Chamfer	u	0.00	13.00																																																																																															
	Thread per Inch	TPI	8 UNC																																																																																																
2					<p>'A' Enlarge View</p>																																																																																														
3																																																																																																			
4																																																																																																			
5																																																																																																			
Dimension as per		B 18.1.1			<table border="1"> <tr> <td colspan="2">Drawing Number</td> <td>SIZE</td> <td>TITLE</td> <td rowspan="2"> </td> <td rowspan="2"> </td> <td rowspan="2"> </td> </tr> <tr> <td colspan="2">KE-BASE-2200-00378-B18.1.1-A193-B7-2.3/4x6.3/4</td> <td>2.3/4"x6.3/4"</td> <td>Stud Bolt</td> </tr> <tr> <td colspan="2">Chemical & Mechanical properties as per</td> <td colspan="3">ASTM A193</td> <td colspan="2">Approved By</td> <td>Drawn By</td> <td>Checked BY</td> </tr> <tr> <td colspan="2">Thread tolerance class (C)</td> <td colspan="3">2A</td> <td colspan="2">Kapil Aggarwal</td> <td>Pankaj Kumar</td> <td>Santosh Kumar</td> </tr> <tr> <td colspan="2">Grade</td> <td colspan="3">B7</td> <td colspan="2">CEO-MD</td> <td>(Sr. QC Manager)</td> <td>Approved By</td> </tr> <tr> <td colspan="2">Weight</td> <td colspan="3">4.53273 kg/piece</td> <td colspan="2">DIMENSIONS ARE IN MILLIMETERS</td> <td colspan="2">KAPIL ENTERPRISES</td> </tr> <tr> <td colspan="2">AMMENDMENT</td> <td colspan="3">Date - 02.08.2018</td> <td colspan="2"> </td> <td colspan="2"> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com </td> </tr> <tr> <td colspan="2">DETAILS</td> <td>REVISION</td> <td colspan="2">DATE</td> <td colspan="2"> ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS </td> <td colspan="2"></td> </tr> <tr> <td colspan="2">REMOVE SHARP EDGES & BURRS</td> <td>SHEET SIZE</td> <td colspan="2">SCALE</td> <td colspan="2"></td> <td colspan="2"></td> </tr> <tr> <td colspan="2"></td> <td>A4</td> <td colspan="2">NTS</td> <td colspan="2"></td> <td colspan="2"></td> </tr> <tr> <td colspan="2"></td> <td colspan="3">FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS</td> <td colspan="2"></td> <td colspan="2"></td> </tr> </table>			Drawing Number		SIZE	TITLE				KE-BASE-2200-00378-B18.1.1-A193-B7-2.3/4x6.3/4		2.3/4"x6.3/4"	Stud Bolt	Chemical & Mechanical properties as per		ASTM A193			Approved By		Drawn By	Checked BY	Thread tolerance class (C)		2A			Kapil Aggarwal		Pankaj Kumar	Santosh Kumar	Grade		B7			CEO-MD		(Sr. QC Manager)	Approved By	Weight		4.53273 kg/piece			DIMENSIONS ARE IN MILLIMETERS		KAPIL ENTERPRISES		AMMENDMENT		Date - 02.08.2018					330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com		DETAILS		REVISION	DATE		ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS				REMOVE SHARP EDGES & BURRS		SHEET SIZE	SCALE								A4	NTS								FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS						
Drawing Number		SIZE	TITLE																																																																																																
KE-BASE-2200-00378-B18.1.1-A193-B7-2.3/4x6.3/4		2.3/4"x6.3/4"	Stud Bolt																																																																																																
Chemical & Mechanical properties as per		ASTM A193						Approved By		Drawn By	Checked BY																																																																																								
Thread tolerance class (C)		2A						Kapil Aggarwal		Pankaj Kumar	Santosh Kumar																																																																																								
Grade		B7			CEO-MD		(Sr. QC Manager)	Approved By																																																																																											
Weight		4.53273 kg/piece			DIMENSIONS ARE IN MILLIMETERS		KAPIL ENTERPRISES																																																																																												
AMMENDMENT		Date - 02.08.2018					330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com																																																																																												
DETAILS		REVISION	DATE		ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS																																																																																														
REMOVE SHARP EDGES & BURRS		SHEET SIZE	SCALE																																																																																																
		A4	NTS																																																																																																
		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS																																																																																																	