

A		B		C	D	E	F	
Parameters		Symbol	Minimum	Maximum				
1	Total Length	L	171.45	174.45				
	Threading Length	l	F.T	F.T				
	Major diameter	D	27.41	28.52				
	Pitch diameter	D1	26.28	26.46				
	Minor diameter	D2	24.63	-				
	Chamfer	u	0.00	6.00				
	Thread per Inch	TPI	8 UNC					
2					<p>'A' Enlarge View</p>			
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		B7M					
	Weight		0.72302 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00153-B18.1.1-A193-B7M-1.1/8x6.3/4				1.1/8"x6.3/4"	Stud Bolt			
AMMENDMENT		Date - 19.07.2018			DIMENSIONS ARE IN MILLIMETERS			
DETAILS	REVISION	DATE			ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	Approved By	Drawn By	Checked BY
REMOVE SHARP EDGES & BURRS		SHEET SIZE	SCALE			Kapil Aggarwal	Pankaj Kumar	Santosh Kumar
		A4	NTS			KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com		
FASTENERS FOR WIND ENERGY		ANCHOR BOLTS & FOUNDATION BOLTS						
A	B	C	D	E	F			