

A		B		C	D	E	F	
Parameters		Symbol	Minimum	Maximum				
1	Total Length	L	101.60	104.60				
	Threading Length	l	F.T	F.T				
	Major diameter	D	34.3900	34.8700				
	Pitch diameter	D1	32.6200	32.8100				
	Minor diameter	D2	30.9700	-				
	Chamfer	u	0.00	7.00				
	Thread per Inch	TPI	8 UNC					
2								
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		B7M					
	Weight		0.64111 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00192-B18.1.1-A193-B7M-1.3/8x4				1.3/8"x4"	Stud Bolt			
AMMENDMENT			Date - 24.07.2018		DIMENSIONS ARE IN MILLIMETERS			
DETAILS		REVISION	DATE		Approved By		Checked BY	
					Kapil Aggarwal CEO-MD		Santosh Kumar	
					Drawn By		Approved By	
					Pankaj Kumar (Sr. QC Manager)		Santosh Kumar	
5	REMOVE SHARP EDGES & BURRS		SHEET SIZE	SCALE	ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS		KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	
			A4	NTS				
		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		APPROVED				
A		B		C	D	E	F	