


A B C D E F

Parameters	Symbol	Minimum	Maximum
Total Length	L	190.50	193.50
Threading Length	l	F.T	F.T
Major diameter	D	34.3900	34.8700
Pitch diameter	D1	32.6200	32.8100
Minor diameter	D2	30.9700	-
Chamfer	u	0.00	7.00
Thread per Inch	TPI	8 UNC	



Dimension as per	B 18.1.1
Chemical & Mechanical properties as per	ASTM A193
Thread tolerance class (C)	2A
Grade	B7M
Weight	1.20208 kg/piece

Drawing Number <b>KE-BASE-2200-00205-B18.1.1-A193-B7M-1.3/8x7.1/2</b>		SIZE <b>1.3/8"x7.1/2"</b>	TITLE <b>Stud Bolt</b>			
AMMENDMENT		Date - 24.07.2018	DIMENSIONS ARE IN MILLIMETERS			Approved By Kapil Aggarwal CEO-MD
DETAILS	REVISION	DATE	<b>ROLL FAST</b> STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	Drawn By Pankaj Kumar (Sr. QC Manager)		Checked BY Approved By Santosh Kumar
<b>REMOVE SHARP EDGES &amp; BURRS</b>	SHEET SIZE <b>A4</b>	SCALE <b>NTS</b>		<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com		

A B C D E F

