

A		B		C	D	E	F
Parameters		Symbol	Minimum	Maximum			
1	Total Length	L	88.90	91.90			
	Threading Length	l	F.T	F.T			
	Major diameter	D	44.01	44.39			
	Pitch diameter	D1	42.14	42.33			
	Minor diameter	D2	40.50	-			
	Chamfer	u	0.00	9.00			
	Thread per Inch	TPI	8 UNC				
2							
3							
4	Dimension as per		B 18.1.1				
	Chemical & Mechanical properties as per		ASTM A193				
	Thread tolerance class (C)		2A				
4	Grade		B7M				
	Weight		0.92089 kg/piece				
Drawing Number				SIZE	TITLE		
KE-BASE-2200-00240-B18.1.1-A193-B7M-1.3/4x3.1/2				1.3/4"x3.1/2"	Stud Bolt		
AMMENDMENT			Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS		
DETAILS		REVISION	DATE		Approved By		Checked BY
					Kapil Aggarwal CEO-MD		Santosh Kumar
					Drawn By		Approved By
					Pankaj Kumar (Sr. QC Manager)		Santosh Kumar
5	REMOVE SHARP EDGES & BURRS		SHEET SIZE	SCALE	ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS		KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com
			A4	NTS			
		Big Bolt Nut		<div style="border: 2px solid green; padding: 5px; text-align: center; color: green; font-weight: bold;">APPROVED</div>			
		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS					
A	B	C	D	E	F		