

A		B		C	D	E	F
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>			
1	Total Length	L	241.30	244.30			
	Threading Length	l	F.T	F.T			
	Major diameter	D	44.01	44.39			
	Pitch diameter	D1	42.14	42.33			
	Minor diameter	D2	40.50	-			
	Chamfer	u	0.00	9.00			
	Thread per Inch	TPI	8 UNC				
2							
3							
4		Dimension as per		B 18.1.1			
		Chemical & Mechanical properties as per		ASTM A193			
		Thread tolerance class (C)		2A			
4		Grade		B7M			
		Weight		2.49956 kg/piece			
5		Drawing Number		SIZE	TITLE		
		KE-BASE-2200-00259-B18.1.1-A193-B7M-1.3/4x9.1/2		1.3/4"x9.1/2"	Stud Bolt		
		AMMENDMENT		Date - 02.08.2018	DIMENSIONS ARE IN MILLIMETERS		
		DETAILS	REVISION	DATE			
		<b>REMOVE SHARP EDGES &amp; BURRS</b>		<b>Big Bolt Nut</b>	<b>ROLL FAST</b>		
		SHEET SIZE	SCALE	FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS	<b>STAINLESS STEEL BOLTS</b> <b>HIGH TENSILE BOLTS</b> PRECISION TURNED COMPONENTS		
		A4	NTS	<b>APPROVED</b>	<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com		
A		B		C	D	E	F