

A		B		C	D	E	F		
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>					
1	Total Length	L	266.70	269.70					
	Threading Length	l	F.T	F.T					
	Major diameter	D	44.01	44.39					
	Pitch diameter	D1	42.14	42.33					
	Minor diameter	D2	40.50	-					
	Chamfer	u	0.00	9.00					
	Thread per Inch	TPI	8 UNC						
4		Dimension as per		B 18.1.1					
		Chemical & Mechanical properties as per		ASTM A193					
		Thread tolerance class (C)		2A					
4		Grade		B7M					
		Weight		2.76268 kg/piece					
Drawing Number				SIZE	TITLE				
KE-BASE-2200-00261-B18.1.1-A193-B7M-1.3/4x10.1/2				1.3/4"x10.1/2"	Stud Bolt				
AMMENDMENT		Date - 02.08.2018			DIMENSIONS ARE IN MILLIMETERS				
DETAILS	REVISION	DATE			<b>ROLL FAST</b> <b>STAINLESS STEEL BOLTS</b> <b>HIGH TENSILE BOLTS</b> PRECISION TURNED COMPONENTS	Approved By Kapil Aggarwal CEO-MD	Drawn By Pankaj Kumar (Sr. QC Manager)	Checked BY Approved By Santosh Kumar	
<b>REMOVE SHARP EDGES &amp; BURRS</b>		SHEET SIZE A4	SCALE NTS			<b>Big Bolt Nut</b> FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS	<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com		
A		B		C	D	E	F		