

A		B		C	D	E	F	
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>				
1	Total Length	L	107.95	110.95				
	Threading Length	l	F.T	F.T				
	Major diameter	D	47.19	47.57				
	Pitch diameter	D1	45.31	45.50				
	Minor diameter	D2	43.67	-				
	Chamfer	u	0.00	10.00				
	Thread per Inch	TPI	8 UNC					
2								
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		B7M					
	Weight		1.38560 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00268-B18.1.1-A193-B7M-1.7/8x4.1/4				1.7/8"x4.1/4"	Stud Bolt			
AMMENDMENT			Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS			
DETAILS		REVISION	DATE		Approved By		Checked BY	
					Kapil Aggarwal CEO-MD		Santosh Kumar	
					Drawn By		Approved By	
					Pankaj Kumar (Sr. QC Manager)		Santosh Kumar	
5	<b>REMOVE SHARP EDGES &amp; BURRS</b>		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		<b>ROLL FAST</b> <b>STAINLESS STEEL BOLTS</b> <b>HIGH TENSILE BOLTS</b> PRECISION TURNED COMPONENTS		<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	
SHEET SIZE		SCALE						
A4		NTS						
A		B		C	D	E	F	

APPROVED