

A		B		C	D	E	F																																																																																																												
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>																																																																																																															
1	Total Length	L	215.90	218.90																																																																																																															
	Threading Length	l	F.T	F.T																																																																																																															
	Major diameter	D	47.19	47.57																																																																																																															
	Pitch diameter	D1	45.31	45.50																																																																																																															
	Minor diameter	D2	43.67	-																																																																																																															
	Chamfer	u	0.00	10.00																																																																																																															
	Thread per Inch	TPI	8 UNC																																																																																																																
2					<p><b>'A' Enlarge View</b></p>																																																																																																														
3																																																																																																																			
4																																																																																																																			
5																																																																																																																			
Dimension as per		B 18.1.1			<table border="1"> <tr> <td colspan="2">Drawing Number</td> <td>SIZE</td> <td>TITLE</td> <td rowspan="2"> </td> <td rowspan="2"> </td> <td rowspan="2"> </td> </tr> <tr> <td colspan="2">KE-BASE-2200-00282-B18.1.1-A193-B7M-1.7/8x8.1/2</td> <td>1.7/8"x8.1/2"</td> <td>Stud Bolt</td> </tr> <tr> <td colspan="2">Chemical &amp; Mechanical properties as per</td> <td colspan="3">ASTM A193</td> <td colspan="2">Approved By</td> <td>Drawn By</td> <td>Checked BY</td> </tr> <tr> <td colspan="2">Thread tolerance class (C)</td> <td colspan="3">2A</td> <td colspan="2">Kapil Aggarwal</td> <td>Pankaj Kumar</td> <td>Santosh Kumar</td> </tr> <tr> <td colspan="2">Grade</td> <td colspan="3">B7M</td> <td colspan="2">CEO-MD</td> <td>(Sr. QC Manager)</td> <td>Approved By</td> </tr> <tr> <td colspan="2">Weight</td> <td colspan="3">2.77120 kg/piece</td> <td colspan="3">KAPIL ENTERPRISES</td> <td></td> </tr> <tr> <td colspan="2">AMMENDMENT</td> <td colspan="3">Date - 02.08.2018</td> <td colspan="3">DIMENSIONS ARE IN MILLIMETERS</td> <td></td> </tr> <tr> <td colspan="2">DETAILS</td> <td>REVISION</td> <td>DATE</td> <td rowspan="3"> </td> <td colspan="3" rowspan="3"> <b>ROLL FAST</b>  <b>STAINLESS STEEL BOLTS</b>  <b>HIGH TENSILE BOLTS</b>            PRECISION TURNED COMPONENTS         </td> <td colspan="2">330 EHTP, HSSIIDC, Kundli Industrial Estate</td> </tr> <tr> <td colspan="2"><b>REMOVE SHARP EDGES &amp; BURRS</b></td> <td>SHEET SIZE</td> <td>SCALE</td> <td colspan="2">Sonepat-Haryana-131028, Ph:9811009061</td> </tr> <tr> <td colspan="2"></td> <td>A4</td> <td>NTS</td> <td colspan="2">Email:-sales@bigboltnut.com, kapil@roll-fast.com</td> </tr> <tr> <td colspan="2">FASTENERS FOR WIND ENERGY</td> <td colspan="3"></td> <td colspan="3"></td> <td colspan="2"></td> </tr> <tr> <td colspan="2">ANCHOR BOLTS &amp; FOUNDATION BOLTS</td> <td colspan="3"></td> <td colspan="3"></td> <td colspan="2"></td> </tr> <tr> <td colspan="2">A</td> <td colspan="2">B</td> <td>C</td> <td>D</td> <td>E</td> <td>F</td> <td colspan="2"></td> </tr> </table>			Drawing Number		SIZE	TITLE				KE-BASE-2200-00282-B18.1.1-A193-B7M-1.7/8x8.1/2		1.7/8"x8.1/2"	Stud Bolt	Chemical & Mechanical properties as per		ASTM A193			Approved By		Drawn By	Checked BY	Thread tolerance class (C)		2A			Kapil Aggarwal		Pankaj Kumar	Santosh Kumar	Grade		B7M			CEO-MD		(Sr. QC Manager)	Approved By	Weight		2.77120 kg/piece			KAPIL ENTERPRISES				AMMENDMENT		Date - 02.08.2018			DIMENSIONS ARE IN MILLIMETERS				DETAILS		REVISION	DATE		<b>ROLL FAST</b> <b>STAINLESS STEEL BOLTS</b> <b>HIGH TENSILE BOLTS</b> PRECISION TURNED COMPONENTS			330 EHTP, HSSIIDC, Kundli Industrial Estate		<b>REMOVE SHARP EDGES &amp; BURRS</b>		SHEET SIZE	SCALE	Sonepat-Haryana-131028, Ph:9811009061				A4	NTS	Email:-sales@bigboltnut.com, kapil@roll-fast.com		FASTENERS FOR WIND ENERGY										ANCHOR BOLTS & FOUNDATION BOLTS										A		B		C	D	E	F		
Drawing Number		SIZE	TITLE																																																																																																																
KE-BASE-2200-00282-B18.1.1-A193-B7M-1.7/8x8.1/2		1.7/8"x8.1/2"	Stud Bolt																																																																																																																
Chemical & Mechanical properties as per		ASTM A193						Approved By		Drawn By	Checked BY																																																																																																								
Thread tolerance class (C)		2A						Kapil Aggarwal		Pankaj Kumar	Santosh Kumar																																																																																																								
Grade		B7M			CEO-MD		(Sr. QC Manager)	Approved By																																																																																																											
Weight		2.77120 kg/piece			KAPIL ENTERPRISES																																																																																																														
AMMENDMENT		Date - 02.08.2018			DIMENSIONS ARE IN MILLIMETERS																																																																																																														
DETAILS		REVISION	DATE		<b>ROLL FAST</b> <b>STAINLESS STEEL BOLTS</b> <b>HIGH TENSILE BOLTS</b> PRECISION TURNED COMPONENTS			330 EHTP, HSSIIDC, Kundli Industrial Estate																																																																																																											
<b>REMOVE SHARP EDGES &amp; BURRS</b>		SHEET SIZE	SCALE					Sonepat-Haryana-131028, Ph:9811009061																																																																																																											
		A4	NTS					Email:-sales@bigboltnut.com, kapil@roll-fast.com																																																																																																											
FASTENERS FOR WIND ENERGY																																																																																																																			
ANCHOR BOLTS & FOUNDATION BOLTS																																																																																																																			
A		B		C	D	E	F																																																																																																												