

A		B		C	D	E	F	
Parameters		Symbol	Minimum	Maximum				
1	Total Length	L	101.60	104.60				
	Threading Length	l	F.T	F.T				
	Major diameter	D	50.3600	50.7400				
	Pitch diameter	D1	48.4800	48.6800				
	Minor diameter	D2	46.8400	-				
	Chamfer	u	0.00	10.00				
	Thread per Inch	TPI	8 UNC					
2								
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		B7M					
	Weight		1.38302 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00292-B18.1.1-A193-B7M-2x4				2"x4"	Stud Bolt			
AMMENDMENT		Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS				
DETAILS	REVISION	DATE				Approved By	Drawn By	
						Kapil Aggarwal	Pankaj Kumar	
						CEO-MD	(Sr. QC Manager)	
						Checked BY		
						Santosh Kumar		
5	REMOVE SHARP EDGES & BURRS		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		ROLL FAST		KAPIL ENTERPRISES	
	SHEET SIZE	SCALE		STAINLESS STEEL BOLTS HIGH TENSILE BOLTS		330 EHTP, HSSIIDC, Kundli Industrial Estate		
	A4	NTS		PRECISION TURNED COMPONENTS		Sonepat-Haryana-131028, Ph:9811009061		
							Email:-sales@bigboltnut.com, kapil@roll-fast.com	
A		B		C	D	E	F	

'A' Enlarge View

APPROVED