

A		B		C	D	E	F	
Parameters		Symbol	Minimum	Maximum				
1	Total Length	L	279.40	282.40				
	Threading Length	l	F.T	F.T				
	Major diameter	D	63.06	63.44				
	Pitch diameter	D1	61.16	61.36				
	Minor diameter	D2	59.54	-				
	Chamfer	u	0.00	12.00				
	Thread per Inch	TPI	8 UNC					
2								
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		B7M					
	Weight		6.02998 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00362-B18.1.1-A193-B7M-2.1/2x11				2.1/2"x11"	Stud Bolt			
AMMENDMENT			Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS			
5	DETAILS	REVISION	DATE		ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	Approved By	Drawn By	Checked BY
	REMOVE SHARP EDGES & BURRS	SHEET SIZE A4	SCALE NTS			FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS	KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	Kapil Aggarwal CEO-MD
A		B		C	D	E	F	