

A		B		C	D	E	F		
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>					
1	Total Length	L	203.20	206.20					
	Threading Length	l	F.T	F.T					
	Major diameter	D	27.41	28.52					
	Pitch diameter	D1	26.28	26.46					
	Minor diameter	D2	24.63	-					
	Chamfer	u	0.00	6.00					
	Thread per Inch	TPI	8 UNC						
2									
3									
4									
5									
Dimension as per		B 18.1.1		<p><b>'A' Enlarge View</b></p>					
Chemical & Mechanical properties as per		ASTM A193							
Thread tolerance class (C)		2A							
4	Grade	B8T							
	Weight	0.85692 kg/piece							
Drawing Number				SIZE	TITLE				
KE-BASE-2200-00156-B18.1.1-A193-B8T-1.1/8x8				1.1/8"x8"	Stud Bolt				
AMMENDMENT		Date - 19.07.2018		DIMENSIONS ARE IN MILLIMETERS		Approved By Kapil Aggarwal CEO-MD			
DETAILS	REVISION	DATE				Drawn By Pankaj Kumar (Sr. QC Manager)			
<b>REMOVE SHARP EDGES &amp; BURRS</b>		<b>Big Bolt Nut</b> FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS				<b>ROLL FAST</b> STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS		Checked BY Approved By Santosh Kumar	
SHEET SIZE	SCALE					<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com			
A4	NTS								
A		B		C	D	E	F		