

A		B		C	D	E	F	
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>				
1	Total Length	L	107.95	110.95				
	Threading Length	l	F.T	F.T				
	Major diameter	D	34.3900	34.8700				
	Pitch diameter	D1	32.6200	32.8100				
	Minor diameter	D2	30.9700	-				
	Chamfer	u	0.00	7.00				
	Thread per Inch	TPI	8 UNC					
2								
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		B8T					
	Weight		0.68118 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00193-B18.1.1-A193-B8T-1.3/8x4.1/4				1.3/8"x4.1/4"	Stud Bolt			
AMMENDMENT			Date - 24.07.2018		DIMENSIONS ARE IN MILLIMETERS			
DETAILS		REVISION	DATE		Approved By			
					Kapil Aggarwal CEO-MD			
					Drawn By			
					Pankaj Kumar (Sr. QC Manager)			
					Checked BY			
					Santosh Kumar			
5	<b>REMOVE SHARP EDGES &amp; BURRS</b>		SHEET SIZE	SCALE	<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com			
			A4	NTS				
			<b>Big Bolt Nut</b> FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		<div style="border: 2px solid green; padding: 5px; text-align: center; color: white; font-weight: bold; font-size: 1.2em;">APPROVED</div> <b>ROLL FAST</b> STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS			
A		B		C	D	E	F	