


Parameters	Symbol	Minimum	Maximum
Total Length	L	241.30	244.30
Threading Length	l	F.T	F.T
Major diameter	D	44.01	44.39
Pitch diameter	D1	42.14	42.33
Minor diameter	D2	40.50	-
Chamfer	u	0.00	9.00
Thread per Inch	TPI	8 UNC	



Dimension as per	B 18.1.1
Chemical & Mechanical properties as per	ASTM A193
Thread tolerance class (C)	2A
Grade	B8T
Weight	2.49956 kg/piece



'A' Enlarge View

Drawing Number KE-BASE-2200-00259-B18.1.1-A193-B8T-1.3/4x9.1/2		SIZE 1.3/4"x9.1/2"	TITLE Stud Bolt			
AMMENDMENT		Date - 02.08.2018	DIMENSIONS ARE IN MILLIMETERS			Approved By Kapil Aggarwal CEO-MD
DETAILS	REVISION	DATE	APPROVED	ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	Drawn By Pankaj Kumar (Sr. QC Manager)	Checked BY Santosh Kumar
REMOVE SHARP EDGES & BURRS	SHEET SIZE A4	SCALE NTS			KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	