

A		B		C	D	E	F
Parameters		Symbol	Minimum	Maximum			
1	Total Length	L	165.10	168.10			
	Threading Length	l	F.T	F.T			
	Major diameter	D	50.3600	50.7400			
	Pitch diameter	D1	48.4800	48.6800			
	Minor diameter	D2	46.8400	-			
	Chamfer	u	0.00	10.00			
	Thread per Inch	TPI	8 UNC				
2							
3							
4	Dimension as per		B 18.1.1				
	Chemical & Mechanical properties as per		ASTM A193				
	Thread tolerance class (C)		2A				
	Grade		B8T				
	Weight		2.24741 kg/piece				
Drawing Number				SIZE	TITLE		
KE-BASE-2200-00302-B18.1.1-A193-B8T-2x6.1/2				2"x6.1/2"	Stud Bolt		
AMMENDMENT		Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS			
DETAILS	REVISION	DATE				Approved By Kapil Aggarwal CEO-MD	Drawn By Pankaj Kumar (Sr. QC Manager)
REMOVE SHARP EDGES & BURRS		SCALE				Checked BY Approved By Santosh Kumar	
A4		NTS				KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	
FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS							
ROLL FAST							
STAINLESS STEEL BOLTS HIGH TENSILE BOLTS							
PRECISION TURNED COMPONENTS							
A		B		C	D	E	F