

A		B		C	D	E	F	
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>				
1	Total Length	L	190.50	193.50				
	Threading Length	l	F.T	F.T				
	Major diameter	D	50.3600	50.7400				
	Pitch diameter	D1	48.4800	48.6800				
	Minor diameter	D2	46.8400	-				
	Chamfer	u	0.00	10.00				
	Thread per Inch	TPI	8 UNC					
2								
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		B8T					
	Weight		2.59316 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00305-B18.1.1-A193-B8T-2x7.1/2				2"x7.1/2"	Stud Bolt			
AMMENDMENT			Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS			
DETAILS		REVISION	DATE		Approved By		Checked BY	
					Kapil Aggarwal CEO-MD		Santosh Kumar	
					Drawn By		Approved By	
					Pankaj Kumar (Sr. QC Manager)		Santosh Kumar	
5	<b>REMOVE SHARP EDGES &amp; BURRS</b>		SHEET SIZE	SCALE	<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com			
			A4	NTS				
		<b>Big Bolt Nut</b>		<div style="border: 2px solid green; padding: 5px; display: inline-block;"> <b>APPROVED</b> </div>				
		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS					<b>ROLL FAST</b> STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	
A		B		C	D	E	F	