

A		B		C	D	E	F
Parameters		Symbol	Minimum	Maximum			
1	Total Length	L	254.00	257.00			
	Threading Length	l	F.T	F.T			
	Major diameter	D	50.3600	50.7400			
	Pitch diameter	D1	48.4800	48.6800			
	Minor diameter	D2	46.8400	-			
	Chamfer	u	0.00	10.00			
	Thread per Inch	TPI	8 UNC				
2							
3							
4	Dimension as per		B 18.1.1				
	Chemical & Mechanical properties as per		ASTM A193				
	Thread tolerance class (C)		2A				
4	Grade		B8T				
	Weight		3.45755 kg/piece				
Drawing Number				SIZE	TITLE		
KE-BASE-2200-00310-B18.1.1-A193-B8T-2x10				2"x10"	Stud Bolt		
AMMENDMENT			Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS		
DETAILS		REVISION	DATE		Approved By		Checked BY
					Kapil Aggarwal CEO-MD		Santosh Kumar
					Drawn By		Approved By
					Pankaj Kumar (Sr. QC Manager)		Santosh Kumar
5	REMOVE SHARP EDGES & BURRS		SHEET SIZE	SCALE	ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS		KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com
			A4	NTS			
FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS				APPROVED			
A		B		C	D	E	F