

A		B		C	D	E	F			
Parameters		Symbol	Minimum	Maximum						
1 Total Length		L	133.35	136.35						
Threading Length		l	F.T	F.T						
Major diameter		D	75.75	76.14						
Pitch diameter		D1	73.85	70.07						
Minor diameter		D2	72.24	-						
Chamfer		u	0.00	15.00						
Thread per Inch		TPI	8 UNC							
2					2					
3								3		
4								4		
5					5			5		
Dimension as per		B 18.1.1			<p>'A' Enlarge View</p>					
Chemical & Mechanical properties as per		ASTM A193								
Thread tolerance class (C)		2A								
Grade		B8T								
Weight		4.24569 kg/piece								
Drawing Number				SIZE	TITLE					
KE-BASE-2200-00397-B18.1.1-A193-B8T-3x5.1/4				3"x5.1/4"	Stud Bolt					
AMMENDMENT		Date - 02.08.2018			DIMENSIONS ARE IN MILLIMETERS					
DETAILS	REVISION	DATE			ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	Approved By	Drawn By	Checked BY		
						Kapil Aggarwal	Pankaj Kumar	Santosh Kumar		
						CEO-MD	(Sr. QC Manager)	Approved By		
REMOVE SHARP EDGES & BURRS		SHEET SIZE	SCALE	KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com						
A4		NTS								
FASTENERS FOR WIND ENERGY										
ANCHOR BOLTS & FOUNDATION BOLTS										
A		B		C	D	E	F			