

A		B		C	D	E	F
Parameters		Symbol	Minimum	Maximum			
1	Total Length	L	266.70	269.70			
	Threading Length	l	F.T	F.T			
	Major diameter	D	75.75	76.14			
	Pitch diameter	D1	73.85	70.07			
	Minor diameter	D2	72.24	-			
	Chamfer	u	0.00	15.00			
	Thread per Inch	TPI	8 UNC				
2					<p>'A' Enlarge View</p>		
3							
4	Dimension as per		B 18.1.1				
	Chemical & Mechanical properties as per		ASTM A193				
	Thread tolerance class (C)		2A				
4	Grade		B8T				
	Weight		8.49138 kg/piece				
Drawing Number				SIZE	TITLE		
KE-BASE-2200-00411-B18.1.1-A193-B8T-3x10.1/2				3"x10.1/2"	Stud Bolt	Approved By Kapil Aggarwal CEO-MD	
AMMENDMENT				Date - 02.08.2018	DIMENSIONS ARE IN MILLIMETERS		Drawn By Pankaj Kumar (Sr. QC Manager)
DETAILS		REVISION	DATE		ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS		
REMOVE SHARP EDGES & BURRS		SHEET SIZE	SCALE				
		A4	NTS				
FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS				KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com			
A	B	C	D	E	F		