

A		B		C	D	E	F	
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>				
1	Total Length	L	190.50	193.50				
	Threading Length	l	F.T	F.T				
	Major diameter	D	31.32	31.70				
	Pitch diameter	D1	29.46	29.63				
	Minor diameter	D2	27.80	-				
	Chamfer	u	0.00	7.00				
	Thread per Inch	TPI	8 UNC					
2								
3								
4		Dimension as per		B 18.1.1				
		Chemical & Mechanical properties as per		ASTM A193				
		Thread tolerance class (C)		2A				
4		Grade		L43				
		Weight		1.00161 kg/piece				
5		Drawing Number		SIZE		TITLE		
		KE-BASE-2200-00180-B18.1.1-A193-L43-1.1/4x7.1/2		1.1/4"x7.1/2"		Stud Bolt		
		AMMENDMENT		Date - 19.07.2018		DIMENSIONS ARE IN MILLIMETERS		
		DETAILS		REVISION		DATE		
		REMOVE SHARP EDGES & BURRS		A4		SCALE NTS		
		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		APPROVED		<b>ROLL FAST</b> <b>STAINLESS STEEL BOLTS</b> <b>HIGH TENSILE BOLTS</b> PRECISION TURNED COMPONENTS		
						<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com		
A		B		C	D	E	F	