

A		B		C	D	E	F	
Parameters		Symbol	Minimum	Maximum				
1	Total Length	L	304.80	307.80				
	Threading Length	l	F.T	F.T				
	Major diameter	D	31.32	31.70				
	Pitch diameter	D1	29.46	29.63				
	Minor diameter	D2	27.80	-				
	Chamfer	u	0.00	7.00				
	Thread per Inch	TPI	8 UNC					
2					<p>'A' Enlarge View</p>			
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		L43					
	Weight		1.60257 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00189-B18.1.1-A193-L43-1.1/4x12				1.1/4"x12"	Stud Bolt			
AMMENDMENT			Date - 19.07.2018		DIMENSIONS ARE IN MILLIMETERS			
5	DETAILS	REVISION	DATE		ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	Approved By	Drawn By	Checked BY
						Kapil Aggarwal	Pankaj Kumar	Santosh Kumar
						CEO-MD	(Sr. QC Manager)	Approved By
	REMOVE SHARP EDGES & BURRS		SHEET SIZE	SCALE	KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com			
	A4	NTS	FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS					
A		B		C	D	E	F	