

| A | | B | | C | D | E | F | |
|-------------------|------------------|---|----------------|--|-------------------------------|--|-------|--|
| Parameters | | Symbol | Minimum | Maximum | | | | |
| 1 | Total Length | L | 177.80 | 180.80 | | | | |
| | Threading Length | l | F.T | F.T | | | | |
| | Major diameter | D | 34.3900 | 34.8700 | | | | |
| | Pitch diameter | D1 | 32.6200 | 32.8100 | | | | |
| | Minor diameter | D2 | 30.9700 | - | | | | |
| | Chamfer | u | 0.00 | 7.00 | | | | |
| | Thread per Inch | TPI | 8 UNC | | | | | |
| 2 | | | | | | | | |
| 3 | | | | | | | | |
| 4 | | Dimension as per | | B 18.1.1 | | | | |
| | | Chemical & Mechanical properties as per | | ASTM A193 | | | | |
| | | Thread tolerance class (C) | | 2A | | | | |
| 4 | | Grade | | L43 | | | | |
| | | Weight | | 1.12194 kg/piece | | | | |
| 5 | | Drawing Number | | KE-BASE-2200-00204-B18.1.1-A193-L43-1.3/8x7 | SIZE | 1.3/8"x7" | TITLE | Stud Bolt |
| | | AMMENDMENT | | Date - 24.07.2018 | DIMENSIONS ARE IN MILLIMETERS | | | |
| | | DETAILS | REVISION | DATE | APPROVED | ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS | | Approved By Kapil Aggarwal CEO-MD |
| | | REMOVE SHARP EDGES & BURRS | | SHEET SIZE A4 | | | | SCALE NTS |
| | | | | FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS | | | | KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com |
| 5 | | | | | | | | |
| A | | B | | C | D | E | F | |