

A		B		C	D	E	F	
Parameters		Symbol	Minimum	Maximum				
1	Total Length	L	107.95	110.95				
	Threading Length	l	F.T	F.T				
	Major diameter	D	37.66	38.04				
	Pitch diameter	D1	35.80	35.98				
	Minor diameter	D2	34.15	-				
	Chamfer	u	0.00	8.00				
	Thread per Inch	TPI	8 UNC					
2								
3								
4		Dimension as per		B 18.1.1				
		Chemical & Mechanical properties as per		ASTM A193				
		Thread tolerance class (C)		2A				
4		Grade		L43				
		Weight		0.82892 kg/piece				
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00218-B18.1.1-A193-L43-1.1/2x4.1/4				1.1/2"x4.1/4"	Stud Bolt			
AMMENDMENT		Date - 02.08.2018			DIMENSIONS ARE IN MILLIMETERS			
DETAILS	REVISION	DATE			ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	Approved By	Drawn By	Checked BY
						Kapil Aggarwal CEO-MD	Pankaj Kumar (Sr. QC Manager)	Santosh Kumar
REMOVE SHARP EDGES & BURRS		SHEET SIZE	SCALE	Big Bolt Nut FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com		
		A4	NTS					
A		B		C	D	E	F	