

A		B		C	D	E	F	
Parameters		Symbol	Minimum	Maximum				
1	Total Length	L	114.30	117.30				
	Threading Length	l	F.T	F.T				
	Major diameter	D	37.66	38.04				
	Pitch diameter	D1	35.80	35.98				
	Minor diameter	D2	34.15	-				
	Chamfer	u	0.00	8.00				
	Thread per Inch	TPI	8 UNC					
2								
3								
4	Dimension as per		B 18.1.1					
	Chemical & Mechanical properties as per		ASTM A193					
	Thread tolerance class (C)		2A					
4	Grade		L43					
	Weight		0.87768 kg/piece					
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00219-B18.1.1-A193-L43-1.1/2x4.1/2				1.1/2"x4.1/2"	Stud Bolt			
AMMENDMENT			Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS			
DETAILS		REVISION	DATE		Approved By Kapil Aggarwal CEO-MD		Drawn By Pankaj Kumar (Sr. QC Manager)	
					Checked BY Approved By Santosh Kumar			
REMOVE SHARP EDGES & BURRS		SHEET SIZE A4	SCALE NTS		ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS		KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	
5			Big Bolt Nut FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS		APPROVED			
A		B		C	D	E	F	