

A		B		C	D	E	F	
Parameters		Symbol	Minimum	Maximum				
1	Total Length	L	133.35	136.35				
	Threading Length	l	F.T	F.T				
	Major diameter	D	44.01	44.39				
	Pitch diameter	D1	42.14	42.33				
	Minor diameter	D2	40.50	-				
	Chamfer	u	0.00	9.00				
	Thread per Inch	TPI	8 UNC					
4		Dimension as per		B 18.1.1				
		Chemical & Mechanical properties as per		ASTM A193				
		Thread tolerance class (C)		2A				
4		Grade		L43				
		Weight		1.38134 kg/piece				
Drawing Number				SIZE	TITLE			
KE-BASE-2200-00247-B18.1.1-A193-L43-1.3/4x5.1/4				1.3/4"x5.1/4"	Stud Bolt			
AMMENDMENT		Date - 02.08.2018			DIMENSIONS ARE IN MILLIMETERS			
DETAILS	REVISION	DATE			ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	Approved By	Drawn By	Checked BY
REMOVE SHARP EDGES & BURRS	SHEET SIZE A4	SCALE NTS				FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS	KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com	Kapil Aggarwal CEO-MD
A		B		C	D	E	F	