

| A | | B | | C | D | E | F |
|-------------------|------------------|---|----------------|-------------------|---|--|---|
| Parameters | | Symbol | Minimum | Maximum | | | |
| 1 | Total Length | L | 228.60 | 231.60 | | | |
| | Threading Length | l | F.T | F.T | | | |
| | Major diameter | D | 56.7100 | 57.0900 | | | |
| | Pitch diameter | D1 | 54.8200 | 55.0300 | | | |
| | Minor diameter | D2 | 53.1900 | - | | | |
| | Chamfer | u | 0.00 | 11.0000 | | | |
| | Thread per Inch | TPI | 8 UNC | | | | |
| 2 | | | | | | | |
| 3 | | | | | | | |
| 4 | | Dimension as per | | B 18.1.1 | | | |
| | | Chemical & Mechanical properties as per | | ASTM A193 | | | |
| | | Thread tolerance class (C) | | 2A | | | |
| 4 | | Grade | | L43 | | | |
| | | Weight | | 4.03202 kg/piece | | | |
| 5 | | Drawing Number | | SIZE | | TITLE | |
| | | KE-BASE-2200-00333-B18.1.1-A193-L43-2.1/4x9 | | 2.1/4"x9" | | Stud Bolt | |
| | | AMMENDMENT | | Date - 02.08.2018 | | DIMENSIONS ARE IN MILLIMETERS | |
| | | DETAILS | | REVISION | | DATE | |
| | | REMOVE SHARP EDGES & BURRS | | A4 | | SCALE NTS | |
| | | FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS | | APPROVED | | ROLL FAST STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS | |
| | | | | | | Approved By Kapil Aggarwal CEO-MD | |
| | | | | | | Drawn By Pankaj Kumar (Sr. QC Manager) | |
| | | | | | | Checked BY Approved By Santosh Kumar | |
| | | | | | | KAPIL ENTERPRISES 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com | |
| A | | B | | C | D | E | F |