

A		B		C	D	E	F				
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>							
1	Total Length	L	266.70	269.70							
	Threading Length	l	F.T	F.T							
	Major diameter	D	63.06	63.44							
	Pitch diameter	D1	61.16	61.36							
	Minor diameter	D2	59.54	-							
	Chamfer	u	0.00	12.00							
	Thread per Inch	TPI	8 UNC								
2											
3											
4		Dimension as per		B 18.1.1							
		Chemical & Mechanical properties as per		ASTM A193							
		Thread tolerance class (C)		2A							
4		Grade		L43							
		Weight		5.75589 kg/piece							
5		Drawing Number		KE-BASE-2200-00361-B18.1.1-A193-L43-2.1/2x10.1/2	SIZE	2.1/2"x10.1/2"	TITLE	Stud Bolt			
		AMMENDMENT		Date - 02.08.2018	DIMENSIONS ARE IN MILLIMETERS			Approved By	Drawn By	Checked BY	
		DETAILS	REVISION	DATE		<b>ROLL FAST</b> STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	Kapil Aggarwal CEO-MD	Pankaj Kumar (Sr. QC Manager)	Santosh Kumar		
		<b>REMOVE SHARP EDGES &amp; BURRS</b>	SHEET SIZE A4	SCALE NTS			<b>Big Bolt Nut</b> FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS	<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com			
A		B		C	D	E	F				