

A		B		C	D	E	F
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>			
1	Total Length	L	266.70	269.70			
	Threading Length	l	F.T	F.T			
	Major diameter	D	69.4100	69.7800			
	Pitch diameter	D1	67.5100	67.7200			
	Minor diameter	D2	65.8900	-			
	Chamfer	u	0.00	13.0000			
	Thread per Inch	TPI	8 UNC				
2							
3							
4	Dimension as per		B 18.1.1				
	Chemical & Mechanical properties as per		ASTM A193				
	Thread tolerance class (C)		2A				
4	Grade		L43				
	Weight		7.05091 kg/piece				
Drawing Number				SIZE	TITLE		
KE-BASE-2200-00386-B18.1.1-A193-L43-2.3/4x10.1/2				2.3/4"x10.1/2"	Stud Bolt		
AMMENDMENT			Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS		
DETAILS		REVISION	DATE		Approved By Kapil Aggarwal CEO-MD		
					Drawn By Pankaj Kumar (Sr. QC Manager)		
					Checked BY Approved By Santosh Kumar		
5	<b>REMOVE SHARP EDGES &amp; BURRS</b>		SHEET SIZE A4	SCALE NTS	<b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com		
		<b>Big Bolt Nut</b>		<div style="border: 2px solid green; padding: 5px; text-align: center; color: white; font-weight: bold;">APPROVED</div>		<b>ROLL FAST</b> STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS	
		FASTENERS FOR WIND ENERGY ANCHOR BOLTS & FOUNDATION BOLTS					
A		B		C	D	E	F