

A		B		C	D	E	F					
<b>Parameters</b>		<b>Symbol</b>	<b>Minimum</b>	<b>Maximum</b>								
1	Total Length	L	88.90	91.90								
	Threading Length	l	F.T	F.T								
	Major diameter	D	75.75	76.14								
	Pitch diameter	D1	73.85	70.07								
	Minor diameter	D2	72.24	-								
	Chamfer	u	0.00	15.00								
	Thread per Inch	TPI	8 UNC									
2					<p><b>'A' Enlarge View</b></p>							
3					<table border="1"> <tr> <td>Dimension as per</td> <td>B 18.1.1</td> </tr> <tr> <td>Chemical &amp; Mechanical properties as per</td> <td>ASTM A193</td> </tr> <tr> <td>Thread tolerance class (C)</td> <td>2A</td> </tr> </table>		Dimension as per	B 18.1.1	Chemical & Mechanical properties as per	ASTM A193	Thread tolerance class (C)	2A
Dimension as per	B 18.1.1											
Chemical & Mechanical properties as per	ASTM A193											
Thread tolerance class (C)	2A											
4		<table border="1"> <tr> <td>Grade</td> <td>L43</td> </tr> <tr> <td>Weight</td> <td>2.83046 kg/piece</td> </tr> </table>		Grade	L43	Weight	2.83046 kg/piece					
Grade	L43											
Weight	2.83046 kg/piece											
Drawing Number				SIZE	TITLE							
KE-BASE-2200-00390-B18.1.1-A193-L43-3x3.1/2				3"x3.1/2"	Stud Bolt	<p>Approved By Kapil Aggarwal CEO-MD</p> <p>Drawn By Pankaj Kumar (Sr. QC Manager)</p> <p>Checked BY Approved By Santosh Kumar</p>						
AMMENDMENT		Date - 02.08.2018		DIMENSIONS ARE IN MILLIMETERS		<p><b>KAPIL ENTERPRISES</b> 330 EHTP, HSSIIDC, Kundli Industrial Estate Sonapat-Haryana-131028, Ph:9811009061 Email:-sales@bigboltnut.com, kapil@roll-fast.com</p>						
DETAILS		REVISION	DATE	<p><b>Big Bolt Nut</b></p> <p>FASTENERS FOR WIND ENERGY ANCHOR BOLTS &amp; FOUNDATION BOLTS</p>		<p><b>ROLL FAST</b></p> <p>STAINLESS STEEL BOLTS HIGH TENSILE BOLTS PRECISION TURNED COMPONENTS</p>						
<p><b>REMOVE SHARP EDGES &amp; BURRS</b></p>		SHEET SIZE A4	SCALE NTS					<p><b>APPROVED</b></p>				
5												
A		B		C	D	E	F					